

EFL 23
HIPOT FOR ELECTRICAL
APPLIANCES TEST
IEC 60335-1 Annex A / IEC 60598-1



SECOM

EFL 23 | HIPOT FOR ELECTRICAL APPLIANCES TEST

IEC 60335-1 Annex A / IEC 60598-1

This equipment is used for the tests of the basic parameters of electrical safety in the end of lines of producing plants of household-electric, electronic equipment, lights, machines tools, etc of high volume. Test makes them of:

The EBE 0 can make this test:

- Ground Tests.
- Dielectric Strenght.
 - + Class I: 1000 Vca.
 - + Class II: 2500 Vca.
- Starting of the equipment.

The system of acquisition and control of data, is based on a microcontroller of last generation mounted on a electronic board development for SE.com: selection, filtrate, processing and measurement of signals.

As much the equipment as this platform was designed for a simple and dynamic handling .

The equipment is given with its Report of calibrations drawn up to national patterns (of optional way) and a



Technical characteristics

- Power Supply: 220Vca, 50Hz (115Vca opcional)
- To use on the table.
- Indicators:
 - Display LCD 2 lines.
 - LEDs of OK o FAULT.
- Totally controlled by microprocessor..
- To Test: Equipment: **Class I** and **Class II**.
- Accessories:
 - Plug Test.
 - Clamp Test.
 - Button box to start the test.
- Verification SET (optional).
- Dimensions:
 - Height: 350mm
 - Width: 350mm
 - Depth: 210mm
- Weight: 22 Kg.
- According to: IEC 60335-1 Annex A.

SECOM reserves the right to change the specifications or design without prior notice.